



Superior Corrosion Control

SCC Step 3 HD Outer Guard



SCC HD Outer Guard is available in a wide range of colors

Description: In any environment there are conditions that may damage coatings such as abrasion, soil stress, frost heave, and mechanical damage. Step 3 HD Outer Guard is a blend of plasticizers and resins saturated into a heavy duty synthetic knit carrier that cures to a hard cast by using the moisture in the surrounding environment. This hard cast provides the protection and added mechanical strength needed to keep the wrap intact and conformed to the metal structure, allowing the wrap to perform to its full potential.

Application Procedure: SCC HD Outer Guard must extend past the existing coating on both ends to ensure strong anchoring. Using the gloves provided, remove Step 3 HD Outer Guard from the packaging and soak in water for 30 seconds. For low temperature applications below 32F soak in low temp activator for 60 seconds. Squeeze the roll to remove excess water and begin tightly spiral wrapping with a 50% overlap over the existing coating. Finally, secure the end of the HD Outer Guard by wrapping it with provided stretch wrap.

Features:

- Easy to apply, minimal surface preparation is required.
- Can be applied to hot or cold surfaces, above or belowground
- Excellent resistance to U.V.
- Provides an excellent profile for painting.
- Increases mechanical protection to any coating system.
- Special open knit material to prevent shielding of Cathodic Protection.

Technical Data:

Properties	English	Metric
Color	Available in multiple colors	Available in multiple colors
Thickness	60 mil avg.	1.5 mm avg.
Maximum Service Temperature	350°F	150°C

Packaging:

Roll Width	Roll Length	ft ² /Roll
4"	15'	5 ft ²
4"	30'	10 ft ²
6"	30'	15 ft ²
6"	50'	25 ft ²
9"	50'	37.5 ft ²



Superior Corrosion Control
201 Andrew Park Drive
Jackson, Michigan 49202
Phone: 1-517-748-9330
Fax: 1-517-784-9331
www.superiorcorrosioncontrol.net

