



Superior Corrosion Control

SCC Pro Mold Putty

Excellent for molding irregular surface for an even application of SCC's Wax Wrap.



Description: Petroleum based anticorrosive filling compound that provides the ability to mold irregular surfaces for an even application of SCC's Wax Wrap.

Application Procedure: To prepare the surface remove all loose scale, rust, paint, and other foreign material. By hand, apply SCC Pro Mold Putty to the surface. Press and mold the material onto the surface ensuring the putty is wetting and adhering. Continue working SCC Pro Mold Putty to the area until desired profile is achieved. Once desired profile is achieved, finish by overwrapping with SCC's Wax Wraps.

Features:

- Only minimal surface preparation is required
- Easily conforms to irregular surfaces
- No curing time needed for immediate service
- Environmentally safe, non toxic, no VOC's
- Will not dry out in heavy clay soils
- Applied over wet or dry surfaces

Technical Data:

Properties	English
Color	Gray
Specific Gravity	1.11
Maximum Service Temperature	200°F
Flash Point	>350°F

Packaging:

2 gallon pails.....Sold Individually



Superior Corrosion Control

201 Andrew Park Drive

Jackson, Michigan 49202

Phone: 1-517-748-9330

Fax: 1-517-784-9331

www.superiorcorrosioncontrol.net